

Recessed Series

Strahman's recessed mixing units are designed to conceal mixing unit piping in a stainless steel box for recessed wall mounting. All exposed parts are stainless steel. These units are ideal for new construction or other places where concealed piping and good looks are desirable.

Specifications

- ◆ **Maximum recommended operating temperature** 200°F/93°C
- ◆ **Maximum working pressure** 150 psi
- ◆ Recessed Series available for:
M-5000TG/5700TG
M-159/750/159TG/750TG
M-358/758

NOTE: When ordering, specify angle valves (back entry) or globe valves (top entry).

Please see reverse side for dimensions.



Shown: Recessed Series with M-5000TG unit; shown with premium hose assembly and red S-70 Series nozzle



USA Headquarters

2801 Baglyos Circle ♦ Bethlehem, PA 18020

Phone: (484) 893-5080 ♦ Fax: (484) 893-5099 ♦ Toll Free: (877) STRAHMAN

www.strahmanvalves.com

France

Savoie Hexapole, F-73420 Mery, France

Tel: 33 (0) 4 79 35 78 00

Fax: 33 (0) 4 79 35 78 20

Germany

Kirchstrasse 16, D-77855, Achern, Germany

Tel: 49 (0) 7841-6846530

Fax: 49 (0) 7841-6846531



ISO 9001
QMI-SAI Global

Recessed Series Dimensions

